Technical Specification/ Product Datasheet

KK-FRP AND KONCRETE PRODUCTS PVT LTD

1114 Hubtown Solaris Prof N.S Phadke Road, Andheri (E) Mumbai-400 069 INDIA Ph: +91 22 66913250 , Mob: +91 9822036550 / 9850089903 , email: info@kkfrp.com / kkmgnsk@gmail.com Web: www.kkfrp.com

Specific Product Code/s:

Product Group:

Sub-Category:

Material Composition :

Basic Dimensions (mm):

Weight (kgs):

Load Rating Classification:

Features:

MCMD02

KK-FRP FIBREGLASS COMPOSITE MANHOLE COVER & FRAME

Durability - Strength -Quality

Medium Duty MD 12.5 T Cap. As per BSEN124:2015

Unsaturated Polyster Resin UV Resistant ISO Grade, Emulsion Fibreglass Matt E Class, Accelators, UV Resistant Pigment, Polymer Concrete in Quartz as Core,

Clear Opening	560 mm Dia
Cover Size:	610 mm Dia
Cover Height:	30 mm
Frame Size:	680 mm Dia
Frame Height:	60 mm

Approx. 30 kg

B125 (12.5T)

FRP Manhole Cover & Frame B125 as per BSEN124.

- Medium duty design to cope with the demands of Medium duty traffic in car parking of residential, commercial areas, Roads, carriageways, etc.
- ≻Key Holes 2nos with (SS Key optional) & Lifting device provided .
- Choice of Colour Available.
- Anti skid surface.
- Waterproof, Weatherproof, Burglar proof, Non corossive, High Strenght to Wt ratio, Easy of handing as Light wt, Heat Resistant, Shockproof.
- ≻ Provision for Logo of Buyer.

Additional Provision of Gasket (O-Ring) 6 mm Dia & SS Nut Bolts

