Technical Specification/ Product Datasheet

KK frp Durability - Strength - Quality

KK-FRP AND KONCRETE PRODUCTS PVT LTD

1114 Hubtown Solaris Prof N.S Phadke Road, Andheri (E) Mumbai-400 069 INDIA

Ph: +91 22 66913250,

Mob: +91 9822036550 / 9850089903,

email: info@kkfrp.com / kkmgnsk@gmail.com

Web: www.kkfrp.com

Specific Product Code/s: MCMD07

Product Group: KK-FRP FIBREGLASS COMPOSITE MANHOLE COVER & FRAME

Sub-Category: Medium Duty MD 12.5 T Cap. As per BSEN124:2015

Material Composition: Unsaturated Polyster Resin UV Resistant ISO Grade, Emulsion

Fibreglass Matt E Class, Accelators, UV Resistant Pigment,

Polymer Concrete in Quartz as Core,

Basic Dimensions (mm): Clear Opening 300 x 300 mm

Cover Size: 350 x 350 mm

Cover Height: 30 mm

Frame Size: 440 x 440 mm

Frame Height: 60 mm

Weight (kgs): Approx. 13 kg

Load Rating Classification: B125 (12.5T)

Features: FRP Manhole Cover & Frame B125 as per BSEN124.

Medium duty design to cope with the demands of Medium duty traffic in car parking of residential, commercial areas, Roads, carriageways, etc.

➤ Key Holes 1nos with (SS Key optional) & Lifting device provided.

Choice of Colour Available.

Anti skid surface.

➤ Waterproof, Weatherproof, Burglar proof, Non corossive, High Strenght to Wt ratio, Easy of handing as Light wt, Heat Resistant, Shockproof.

➤ Provision for Logo of Buyer.

➤ Additional Provision of Gasket (O-Ring) 6 mm Dia & SS Nut Bolts

