

## Technical Specification/ Product Datasheet

## KK-FRP AND KONCRETE PRODUCTS PVT LTD

1114 Hubtown Solaris Prof N.S Phadke Road, Andheri (E) Mumbai-400 069 INDIA

Ph: +91 22 66913250,

Mob: +91 9822036550 / 9850089903,

email: info@kkfrp.com / kkmgnsk@gmail.com

Web: www.kkfrp.com

Specific Product Code/s: GGLD-02

Product Group: KK-FRP FIBREGLASS COMPOSITE STORM WATER GRATING COVER & FRAME

Sub-Category: Light Duty LD 2.5 T Cap. As per BSEN124:2015

Material Composition: Unsaturated Polyster Resin UV Resistant ISO Grade, Emulsion

Fibreglass Matt É Class, Accelators, UV Resistant Pigment,

Polymer Concrete in Quartz as Core,

Basic Dimensions (mm): Clear Opening 300 x 300 mm

Cover Size: 360 x 360 mm

Cover Height: 30 mm

Frame Size: 440 x 440 mm

Frame Height: 60 mm

Weight (kgs): Approx. 13 kg

Load Rating Classification: LD-2.5T

Features: FRP Manhole Cover & Frame LD-2.5T as per BSEN124.

Light duty design to cope with the demands of Light duty traffic in foot paths ,cycle tracks ,car parking of residential

areas etc.

Choice of Colour Available.

Anti skid surface.


➤ Waterproof, Weatherproof, Burglar proof, Non corossive, High Strenght to Wt ratio, Easy of handing as Light wt,

Heat Resistant, Shockproof .

➤ Provision for Logo of Buyer.



## DETAILED DRAWING KK-FRP COMPOSITE STORM WATER GRATING COVER & FRAME CLEAR OPENING 300 X 300 MM CAP 2.5T



## **SECTION AA**

ALL DIMENSIONS IN MM, DIMENSIONAL TOLERANCE +/- 1%.

CLEAR OPENING (300 X 300)	A
OUTER COVER SIZE (360 X 360)	B
OUTER FRAME SIZE (440 X 440)	D
COVER THICKNESS (30)	C
FRAME THICKNESS (60)	E
Approx. Weight 13 kg	