

Technical Specification/ Product Datasheet

GGLD-06

KK-FRP AND KONCRETE PRODUCTS PVT LTD

1114 Hubtown Solaris Prof N.S Phadke Road, Andheri (E) Mumbai-400 069 INDIA Ph: +91 22 66913250 , Mob: +91 9822036550 / 9850089903 , email: info@kkfrp.com / kkmgnsk@gmail.com Web: www.kkfrp.com

Specific Product Code/s:



Product Group:	KK-FRP FIBREGLASS COMPOSITE STORM WATER GRATING COVER & FRAME
Sub-Category:	Light Duty LD 2.5 T Cap. As per BSEN124:2015
Material Composition :	Unsaturated Polyster Resin UV Resistant ISO Grade, Emulsion Fibreglass Matt E Class, Accelators, UV Resistant Pigment, Polymer Concrete in Quartz as Core,
Basic Dimensions (mm):	Clear Opening600 x 600 mmCover Size:660 x 660 mmCover Height:30 mmFrame Size:750 x 750 mmFrame Height:70 mm
Weight (kgs):	Approx. 43 kg
Load Rating Classification:	LD-2.5T
Features:	 FRP Manhole Cover & Frame LD-2.5T as per BSEN124. Light duty design to cope with the demands of Light duty traffic in foot paths ,cycle tracks ,car parking of residential areas etc. Choice of Colour Available. Anti skid surface. Waterproof, Weatherproof, Burglar proof , Non corossive, High Strenght to Wt ratio, Easy of handing as Light wt , Heat Resistant, Shockproof . Provision for Logo of Buyer.



A

В

D

C

E

DETAILED DRAWING KK-FRP COMPOSITE STORM WATER GRATING COVER & FRAME CLEAR OPENING 600 X 600 MM CAP 2.5T

