


Technical Specification/ Product Datasheet







KK-FRP AND KONCRETE PRODUCTS PVT LTD



1114 Hubtown Solaris
Prof N.S Phadke Road, Andheri (E)
Mumbai-400 069
INDIA
Ph: +91 22 66913250 ,
Mob: +91 9822036550 / 9850089903 ,
email: info@kkfrp.com / kkmgnsk@gmail.com
Web: www.kkfrp.com



Specific Product Code/s:	MCLD15
Product Group:	KK-FRP FIBREGLASS COMPOSITE MANHOLE COVER & FRAME
Sub-Category:	Light Duty LD 2.5/5 T Cap. As per BSEN124:2015
Material Composition :	Unsaturated Polyester Resin UV Resistant ISO Grade, Emulsion Fibreglass Matt E Class, Accelerators, UV Resistant Pigment, Polymer Concrete in Quartz as Core,
Basic Dimensions (mm):	Clear Opening 900 x 750 mm Cover Size: 960 x 810 mm Cover Height: 30 mm Frame Size: 1030 x 880 mm Frame Height: 70 mm
Weight (kgs):	Approx. 75 kg
Load Rating Classification:	LD-2.5/5T
Features:	<ul style="list-style-type: none">➤ FRP Manhole Cover & Frame LD-2.5/5T as per BSEN124.➤ Light duty design to cope with the demands of Light duty traffic in foot paths ,cycle tracks ,car parking of residential areas etc.➤ Key Holes 2nos with (SS Key optional) & Lifting device provided .➤ Choice of Colour Available.➤ Anti skid surface.➤ Waterproof, Weatherproof, Burglar proof,Non corossive, High Strenght to Wt ratio, Easy of handing as Light wt , Heat Resistant, Shockproof .➤ Provision for Logo of Buyer.➤ Additional Provision of Gasket (O-Ring) 6 mm Dia & SS Nut Bolts with Washer to make Water Tight (Optional) .




DETAIL B



DETAIL C
KEY HOLE
FOR LIFTING

- ① CLEAR OPENING = 900 x 750 MM
- ② OUTER FRAME SIZE = 1050 x 900 x 70 MM
- ③ OUTER COVER SIZE = 960 x 810 x 30 MM
- ④ APPROX WEIGHT = 80 KG

 	Drawn RJ	Ched AB	SCALE: 1:5		DRG. NO. MCLD-15-900x750 2.5 T
DESCRIPTION: MCLD-15			Sheet No. 2 OF 2		
					

NOTE:-
1. ALL DIMENSIONS ARE IN MM.
2. DIMENSIONAL TOLERANCE +/- 1%

CONFIDENTIAL INFORMATION
(UNAUTHORISED DISCLOSURE PROHIBITED)

KK frp