Technical Specification/ **Product Datasheet**

KK-FRP AND KONCRETE PRODUCTS PVT LTD

1114 Hubtown Solaris Prof N.S Phadke Road, Andheri (E) Mumbai-400 069 INDIA

Ph: +91 22 66913250,

Mob: +91 9822036550 / 9850089903,

email: info@kkfrp.com / kkmgnsk@gmail.com

Web: www.kkfrp.com

Specific Product Code/s: WTCF HD-10 Water & Air Tight Tank Covers & Frames

Product Group: KK-FRP FIBREGLASS COMPOSITE MANHOLE COVER & FRAME

Sub-Category: Heavy Duty HD 20T Cap. As per BSEN124:2015

Material Composition: Unsaturated Polyster Resin UV Resistant ISO Grade, Emulsion

Fibreglass Matt É Class, Accelators, UV Resistant Pigment,

Polymer Concrete in Quartz as Core,

Basic Dimensions (mm): Clear Opening 1200X1200 mm

> Cover Size: 1280X1280 mm

Cover Height: 60 mm

Frame Size: 1200X1200 mm

Frame Height: 90_{mm}

Weight (kgs): Approx. 255kg

Load Rating Classification: HD (20T)

FRP Manhole Cover & Frame HD as per BSEN124. Features:

> ➤ Heavy duty design to cope with the demands of Heavy duty traffic in car parking of residential, commercial areas, Roads, carriageways, etc.

➤ Key Holes 2nos with (SS Key optional) & Lifting device provided.

Choice of Colour Available.

>Anti skid surface.

➤ Waterproof, Weatherproof, Burglar proof, Non corossive, High Strenght to Wt ratio, Easy of handing as Light wt,

Heat Resistant, Shockproof.


➤ Provision for Logo of Buyer.

Additional Provision of Gasket (O-Ring) 6 mm Dia & SS Nut Bolts with Washer to make Water Tight (Optional).

DETAILED DRAWING KK-FRP COMPOSITE WATER & AIR TIGHT MANHOLE COVER & FRAME WITH NUT & BOLT FASTENERS & O RING - HEAVY DUTY

Durability - Strength -Quality

CLEAR OPENING 1200X1200 MM CAP 20T



SECTION AA

