

Technical Specification/ Product Datasheet




KK-FRP AND KONCRETE PRODUCTS PVT LTD

1114 Hubtown Solaris
Prof N.S Phadke Road, Andheri (E)
Mumbai-400 069
INDIA
Ph: +91 22 66913250 ,
Mob: +91 9822036550 / 9850089903 ,
email: info@kkfrp.com / kkmgnsk@gmail.com
Web: www.kkfrp.com




| | |
|-----------------------------|---|
| Specific Product Code/s: | WTCF LD-07 Water & Air Tight Tank Covers & Frames |
| Product Group: | KK-FRP FIBREGLASS COMPOSITE MANHOLE COVER & FRAME |
| Sub-Category: | Ligth Duty LD 2.5T Cap. As per BSEN124:2015 |
| Material Composition : | Unsaturated Polyster Resin UV Resistant ISO Grade, Emulsion Fibreglass Matt E Class, Accelators, UV Resistant Pigment, Polymer Concrete in Quartz as Core, |
| Basic Dimensions (mm): | Clear Opening 900X600 mm Cover Size: 980X680 mm Cover Height: 50 mm Frame Size: 1080X780 mm Frame Height: 80mm |
| Weight (kgs): | Approx. 10kg |
| Load Rating Classification: | LD (2.5T) |
| Features: | <ul style="list-style-type: none">➤ FRP Manhole Cover & Frame LD as per BSEN124.➤ Light duty design to cope with the demands of Light duty traffic in car parking of residential, commercial areas , Roads , carriageways, etc.➤ Key Holes 2nos with (SS Key optional) & Lifting device provided .➤ Choice of Colour Available.➤ Anti skid surface.➤ Waterproof, Weatherproof, Burglar proof, Non corrosive, High Strenght to Wt ratio, Easy of handing as Light wt , Heat Resistant, Shockproof .➤ Provision for Logo of Buyer.➤ Additional Provision of Gasket (O-Ring) 6 mm Dia & SS Nut Bolts with Washer to make Water Tight (Optional) . |



DETAILED DRAWING
KK-FRP COMPOSITE WATER & AIR TIGHT MANHOLE COVER & FRAME
WITH NUT & BOLT FASTENERS & O RING - LIGHT DUTY
CLEAR OPENING 900X600 MM CAP 2.5T



PLAN



ALL DIMENSIONS IN MM, DIMENSIONAL TOLERANCE +/- 1%.

SECTION AA

| | |
|------------------------------------|------------|
| CLEAR OPENING (900X600) | (A) |
| OUTER COVER SIZE (980X680) | (B) |
| OUTER FRAME SIZE (1080X780) | (D) |
| COVER THICKNESS (50) | (C) |
| FRAME THICKNESS (80) | (E) |
| Approx. Weight 100kg | |