

# Technical Specification/ Product Datasheet



## KK-FRP AND KONCRETE PRODUCTS PVT LTD


1114 Hubtown Solaris  
Prof N.S Phadke Road, Andheri (E)  
Mumbai-400 069  
INDIA  
Ph: +91 22 66913250 ,  
Mob: +91 9822036550 / 9850089903 ,  
email: [info@kkfrp.com](mailto:info@kkfrp.com) / [kkmgnsk@gmail.com](mailto:kkmgnsk@gmail.com)  
Web: [www.kkfrp.com](http://www.kkfrp.com)

Specific Product Code/s:	WTCTF LD-09 Water & Air Tight Tank Covers & Frames
Product Group:	KK-FRP FIBREGLASS COMPOSITE MANHOLE COVER & FRAME
Sub-Category:	Ligth Duty LD 2.5T Cap. As per BSEN124:2015
Material Composition :	Unsaturated Polyester Resin UV Resistant ISO Grade, Emulsion Fibreglass Matt E Class, Accelerators, UV Resistant Pigment, Polymer Concrete in Quartz as Core,
Basic Dimensions (mm):	Clear Opening 1000X1000 mm Cover Size: 1080X1080 mm Cover Height: 50 mm Frame Size: 1200X1200 mm Frame Height: 80mm
Weight (kgs):	Approx. 170kg
Load Rating Classification:	LD (2.5T)
Features:	<ul style="list-style-type: none"><li>➤ FRP Manhole Cover &amp; Frame LD as per BSEN124.</li><li>➤ Light duty design to cope with the demands of Light duty traffic in car parking of residential, commercial areas , Roads , carriageways, etc.</li><li>➤ Key Holes 2nos with <b>(SS Key optional)</b> &amp; Lifting device provided .</li><li>➤ Choice of Colour Available.</li><li>➤ Anti skid surface.</li><li>➤ Waterproof, Weatherproof, Burglar proof, Non corrosive, High Strenth to Wt ratio, Easy of handing as Light wt , Heat Resistant, Shockproof .</li><li>➤ Provision for Logo of Buyer.</li><li>➤ Additional Provision of Gasket (O-Ring) 6 mm Dia &amp; SS Nut Bolts with Washer to make Water Tight <b>(Optional)</b> .</li></ul>






# DETAILED DRAWING

## KK-FRP COMPOSITE WATER & AIR TIGHT MANHOLE COVER & FRAME WITH NUT & BOLT FASTENERS & O RING - LIGHT DUTY CLEAR OPENING 1000X1000 MM CAP 2.5T



**PLAN**



ALL DIMENSIONS IN MM, DIMENSIONAL TOLERANCE +/- 1%.

### SECTION AA

CLEAR OPENING (1000X1000)	(A)
OUTER COVER SIZE (1080X1080)	(B)
OUTER FRAME SIZE (1200X1200)	(D)
COVER THICKNESS (50)	(C)
FRAME THICKNESS (90)	(E)
<b>Approx. Weight 170 kg</b>	