

Technical Specification/ Product Datasheet



KK-FRP AND KONCRETE PRODUCTS PVT LTD

1114 Hubtown Solaris
Prof N.S Phadke Road, Andheri (E)
Mumbai-400 069
INDIA
Ph: +91 22 66913250 ,
Mob: +91 9822036550 / 9850089903 ,
email: info@kkfrp.com / kkmgnsk@gmail.com
Web: www.kkfrp.com



Specific Product Code/s:	WTCF MD-03 Water & Air Tight Tank Covers & Frames
Product Group:	KK-FRP FIBREGLASS COMPOSITE MANHOLE COVER & FRAME
Sub-Category:	Medium Duty MD 10T Cap. As per BSEN124:2015
Material Composition :	Unsaturated Polyester Resin UV Resistant ISO Grade, Emulsion Fibreglass Matt E Class, Accelerators, UV Resistant Pigment, Polymer Concrete in Quartz as Core,

Basic Dimensions (mm):	Clear Opening	450X450 mm
	Cover Size:	530X530 mm
	Cover Height:	50 mm
	Frame Size:	630X630 mm
	Frame Height:	80mm
Weight (kgs):	Approx. 45kg	


Load Rating Classification:	MD (10T)
-----------------------------	----------

Features:	<ul style="list-style-type: none">➤ FRP Manhole Cover & Frame MD as per BSEN124.➤ Medium duty design to cope with the demands of Medium duty traffic in car parking of residential, commercial areas , Roads , carriageways, etc.➤ Key Holes 2nos with (SS Key optional) & Lifting device provided .➤ Choice of Colour Available.➤ Anti skid surface.➤ Waterproof, Weatherproof, Burglar proof, Non corrosive, High Strength to Wt ratio, Easy of handing as Light wt , Heat Resistant, Shockproof .➤ Provision for Logo of Buyer.➤ Additional Provision of Gasket (O-Ring) 6 mm Dia & SS Nut Bolts
-----------	---






DETAILED DRAWING

KK-FRP COMPOSITE WATER & AIR TIGHT MANHOLE COVER & FRAME WITH NUT & BOLT FASTENERS & O RING - MEDIUM DUTY CLEAR OPENING 450X450 MM CAP 10T



PLAN



ALL DIMENSIONS IN MM, DIMENSIONAL TOLERANCE +/- 1%.

SECTION AA

CLEAR OPENING (450X450)	(A)
OUTER COVER SIZE (530X530)	(B)
OUTER FRAME SIZE (630X630)	(D)
COVER THICKNESS (50)	(C)
FRAME THICKNESS (80)	(E)
Approx. Weight 45kg	